



Globe Power's Metro GP43K Solar Lighting Tower has been built to suit various industries and is compliant with metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Jack pads
- Audio safety messages
- Fire extinguisher
- Emergency stop
- Isolators
- Tilt sensor
- AC charger
- Wheel chocks
- Tie down points
- Lifting points



 **USER-FRIENDLY
OPERATION INTERFACE**

 **SOLAR & ADVANCED
LITHIUM ION BATTERY**

 **PORTABLE & EASY TO
TRANSPORT**

 **AUSTRALIAN DESIGNED
& ENGINEERED**

PRODUCT SPECIFICATIONS

GENERAL

Model	Metro GP43K
Lumen Output	43,000
Mast Height	24.6 feet
Mast Type	Hydraulic/Cable
Lights	2 x 200w LED Modules (Dimmable)
Coverage	295.3 x 328.1ft at 5 lux

OPERATIONAL DATA

Wind Rating	62.1 mph
Working Temperature	32° to 122°F
Light Bar Tilt	0 to 90° Electric
Light Bar Rotation	355° Electric
Stabiliser Supports	4 x Manual Rotatable

BATTERY

Battery	10.24kWh Lithium LFP
Run Time	42 hours
Solar	1.35kWp
Solar Tilt	45°
Solar Efficiency	1 hr of sun/4 hrs of light

UNIT INFORMATION

Dimensions (Towing)	131.9" x 57.9" x 117.5" (LxWxH)
Dimensions (Stowed)	89.0" x 57.9" x 117.5" (LxWxH)
Dimensions (Deployed)	89.0" x 132.3" x 313.9" (LxWxH)
Weight	2,866lbs
Trailer Type	Single Axle
Security	Wheel/hitch locks, wheel clamp, folding drawbar, security wheel nuts

