





Globe Power's Eco GP56K Solar Lighting Tower has been built to suit various industries and is compliant with metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Folding drawbar
- Solar tilt
- Fire extinguisher
- Emergency stop
- Isolators
- AC charger
- Wheel chocks
- Tie down points
- Lifting points
- Mudguards



 USER-FRIENDLY OPERATION INTERFACE

 SOLAR & ADVANCED LITHIUM ION BATTERY

 PORTABLE & EASY TO TRANSPORT

 AUSTRALIAN DESIGNED & ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

Model	Eco - GP56k
Lumen Output	56,000
Mast Height	24.6 feet
Mast Type	Hydraulic/Cable
Lights	2 x 200w LED Modules (Dimmable)
Coverage	360.9 x 328.1ft at 5 lux

OPERATIONAL DATA

Wind Rating	62.1 mph
Working Temperature	32 to 122°F
Light Bar Tilt	0 to 90° Electric
Light Bar Rotation	355° Electric
Stabiliser Supports	4 x Manual

BATTERY

Battery	10.8kWh Deep Cycle Gel
Run Time	30 hours
Solar	1.23kWp
Solar Tilt	30° to 45°
Solar Efficiency	1 hour of sun/3 hours of light

UNIT INFORMATION

Dimensions (Transport)	123.6" x 59.1" x 114.2" (LxWxH)
Dimensions (Deployed)	86.6" x 136.0" x 301.2" (LxWxH)
Dimensions (Stowed)	86.6" x 59.1" x 114.2" (LxWxH)
Weight	3,196.7bs
Trailer Type	Single Axle
Tyre & Rim Size	215/70R15
Security	Wheel/hitch locks, wheel clamp, security wheel nuts

