

KEY FEATURES

Globe Power’s Urban GP65K Solar Lighting Tower has been built to suit various industries and is compliant with metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Jack pads
- Audio safety messages
- Fire extinguisher
- Emergency stop
- Isolators
- Tilt sensor
- AC charger
- Wheel chocks
- Tie down points
- Lifting points



USER-FRIENDLY  
OPERATION INTERFACE

SOLAR & ADVANCED  
LITHIUM ION BATTERY

PORTABLE & EASY TO  
TRANSPORT

AUSTRALIAN DESIGNED  
& ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

Model	Urban GP65K
Lumen Output	65,000
Mast Height	29.5 feet
Mast Type	Hydraulic/Cable
Lights	4 x 150w LED Modules (Dimmable)
Coverage	393.7x 393.7ft at 5 lux

OPERATIONAL DATA

Wind Rating	62.1 mph
Working Temperature	32° to 122°F
Light Bar Tilt	0 to 90° Electric
Light Bar Rotation	355° Electric
Stabiliser Supports	4 x Manual

BATTERY

Battery	14.4kWh AGM
Run Time	48 hours
Solar	1.78kWp
Solar Tilt	30°
Solar Efficiency	1 hr of sun/3.5 hrs of light

UNIT INFORMATION

Dimensions (Transport)	144.1" x 88.2" x 115.4" (LxWxH)
Dimensions (Deployed)	11.8" x 14.3" x 31.8" (LxWxH)
Weight	4,188.8bs
Trailer Type	Single Axle
Tyre & Rim Size	15'
Security	Wheel/hitch locks, wheel clamp, security wheel nuts

