



Globe Power's Metro GP43K Solar Lighting Tower has been built to suit various industries and is compliant with metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Jack pads
- Audio safety messages
- Fire extinguisher
- Emergency stop
- Isolators
- Tilt sensor
- AC charger
- Wheel chocks
- Tie down points
- Lifting points



 USER-FRIENDLY OPERATION INTERFACE

 SOLAR & ADVANCED LITHIUM ION BATTERY

 PORTABLE & EASY TO TRANSPORT

 AUSTRALIAN DESIGNED & ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

| | |
|--------------|---------------------------------|
| Model | Metro GP43K |
| Lumen Output | 43,000 |
| Mast Height | 25 feet |
| Mast Type | Hydraulic/Cable |
| Lights | 2 x 200w LED Modules (Dimmable) |
| Coverage | 295 x 328ft at 5 lux |

OPERATIONAL DATA

| | |
|---------------------|----------------------|
| Wind Rating | 62.1mi/h |
| Working Temperature | 32° to 122°F |
| Light Bar Tilt | 0 to 90° Electric |
| Light Bar Rotation | 355° Electric |
| Stabiliser Supports | 4 x Manual Rotatable |

BATTERY

| | |
|------------------|----------------------------|
| Battery | 10.24kWh Lithium LFP |
| Run Time | 42 hours |
| Solar | 1.35kWp |
| Solar Tilt | 45° |
| Solar Efficiency | 1 hr of sun/4 hrs of light |

UNIT INFORMATION

| | |
|-----------------------|--|
| Dimensions (Towing) | 132" x 58" x 117" (LxWxH) |
| Dimensions (Stowed) | 89" x 58" x 117" (LxWxH) |
| Dimensions (Deployed) | 89" x 132" x 314" (LxWxH) |
| Weight | 2,866lbs |
| Trailer Type | Single Axle |
| Security | Wheel/hitch locks, wheel clamp, folding drawbar, security wheel nuts |

