



Globe Power Mobile AC units are industrial grade power banks, which utilise a range of different power sources (solar, grid, genset, battery input) to provide portable AC power. Quick installation will result in a permanent power solution with a 10 year battery life, that is low maintenance, and provides exceptional return on investment.

Globe Power's use of the best components can all be remotely monitored to see power consumption and battery life.



Powered by



PRODUCT SPECIFICATIONS

GENERAL

Model	MAC20K2-30
Voltage	120/240v AC Split Phase
Output Power	20kVA @ 77°F, 16.3kVA @ 104°F
Frequency	60Hz

BATTERY

Battery Type	Solartech - Lithium Iron Phosphate
Battery Voltage	48V DC
AC Output Capacity	25kWh
Recharge Time	3 hours (10-100%)

OPERATIONAL DATA

Operating Temperature	32°F - 122°F
Altitude	0 - 4921ft (>4921ft derating)
IP Rating	NEMA 3S
Input	50A NEMA 14 - 50L
Output	50A Nema 14 - 50R

INPUTS

Solar Input	4kWp max. 250v max
Generator/Grid	Remote Start feature,

UNIT

Dimensions (HxWxD)	70" x 53" x 28"
Weight	2200 lbs

GPUSA-MAC20K2-30-V1.1