


# HYBRID LIGHTING TOWER GP160K-H MINI HYBRID



Globe Power's GP160K-H Mini Hybrid LED Mobile Lighting Tower, equipped with a battery/alternator system, delivers 160,000 lumens of light with a 65% reduction in engine use, providing 3 times the service intervals and engine life. This unit features a compact design, ensuring ease of operation, transport and reliability in any environment.



## PRODUCT SPECIFICATIONS

### GENERAL

Model	GP160K-H Mini Hybrid
Light Power	4 x 300w LED (Dimmable)
Light Output	163,000 Lumens
Mast Height	23 feet
Mast Rotation	355° Electric Rotation
Light Bar Tilt	0° - 90° Electric Tilt
Features	Dusk Sensor, Fire Extinguisher, Level Sensor, Door Safety Switches, Isolators, Jump Start Receptacle, Wheel Chocks, Fork Pockets, 7 Day Timer, Remote Monitoring, Auto Lower Mast

### GENSET


Engine	Kubota Z482 - T4
Fuel Type	Diesel
Fuel Tank Capacity	29 Gal, fully bunded
Fuel Consumption	0.1 Gal/hr*
Running Time	250 hours*
Alternator	Meccalte PMG - 3kW
Battery	5kWh - 48v LFP Battery
Noise Level	68db at 23ft
Control Panel	Smartgen lighting tower controller

### OPERATIONAL

Wind Rating	62mph
Mast Operation	Hydraulic lifting system
Stabiliser Support	4 x Manually adjustable

### UNIT INFORMATION

Dimensions (Stowed)	73" x 56" x 92" (LxWxH)
Dimensions (Deployed)	89" x 66" x 280" (LxWxH)
Weight	2811lbs
Trailer Type	Single Axle, electric brake
Lifting Points	1



\*Based on full light output

GPUSA-GP160K-H Mini Hybrid-V4-1125

© 2025 All information and imagery contained in this brochure is the property of Globe Power.

This document is for informational purposes only. Globe Power reserves the right to make changes without further notice to any information herein. The content is provided as is and without express or implied warranties of any kind.