

Globe Power's GP160k Mini LED Mobile Lighting Tower, equipped with a 2.5kW generator, delivers 163,000 lumens of light. This unit features a compact system, ensuring ease of operation and reliability in any environment



PRODUCT SPECIFICATIONS

GENERAL

Model	GP160k Mini
Light Power	4 x 300w LED (Dimmable)
Light Output	163,000 Lumens
Mast Height	23 feet
Mast Rotation	355° Electric Rotation
Light Bar Tilt	0° - 90° Electric Tilt
Features	Dusk Sensor, Fire Extinguisher, Level Sensor, Door Safety Switches, Isolators, Jump Start Receptacle, Remote Monitoring, 7 Day Timer

GENSET

Engine	Kubota Z482 - Stage V
Fuel Type	Diesel
Fuel Tank Capacity	31.7 gal, fully bunded
Fuel Consumption	0.16 gal/hr
Running Time	191 hours
Alternator	Meccalte PM5G 25/20
Noise Level	60db at 23ft
Control Panel	Smartgen lighting tower controller

OPERATIONAL

Wind Rating	62mph
Mast Operation	Hydraulic lifting system
Stabiliser Support	4 x Manually adjustable

UNIT INFORMATION

Dimensions (Stowed)	74" x 56" x 92" (LxWxH)
Dimensions (Deployed)	89" x 88" x 280" (LxWxH)
Weight	2,700lbs
Trailer Type	Single Axle, electrical brake
Lifting Points	1

