



MOBILE AC SERIES MAC5K-10



Globe Power Mobile AC units are industrial grade power banks, which utilise a range of different power sources (solar, grid, genset, battery input) to provide portable AC power. Quick installation will result in a permanent power solution with a 10 year battery life, that is low maintenance, and provides exceptional return on investment.

Globe Power's use of the best components can all be remotely monitored to see power consumption and battery life.



Powered by



PRODUCT SPECIFICATIONS

GENERAL

Model	MAC5K-10
Voltage	120v AC Input, 120V AC Output
Output Power	4.0kW continuous load, 9kW peak
Frequency	60Hz

BATTERY

Battery Type	Solartech - Lithium Iron Phosphate
Battery Voltage	51.2V DC
Battery Capacity	10.2kWh
Recharge Time	4 hours (10-100%)
Monitoring	5" Touchscreen, Remote cloud monitoring
Features	Heating & Air Conditioning

OPERATIONAL DATA

Operating Temperature	14°F - 122°F
Altitude	0 - 4921ft (>4921ft derating)
IP Rating	NEMA 3S
Input	1 x 120v 50A Inlet, 1 x 120v 50A Outlet - 1 x 5-15 GFCI Twin Outlet, 1 x 5-20 GFCI Twin Outlet

INPUTS

Solar Input	4kWp max. 250v max.
Generator/Grid	Remote Start feature, 6kW input

UNIT

Dimensions (HxWxD)	52" x 36" x 42"
Weight	790 lbs

GPUSA-MAC5k10-V3-1225