SECURITY & COMMUNICATIONS

ECO HYBRID LTE



KEY FEATURES

Globe Power's Eco Hybrid LTE Solar Comms Tower has been built to suit various industries and with a Hatz backup engine it can run in any weather.

- Folding drawbar
- Solar tilt
- Level alarm & lockout
- Fire extinguisher
- Emergency stop
- Isolators
- AC charger
- Wheel chocks
- Tie down points
- Lifting points
- 4 x Jack pads
- E-Brake

USER-FRIENDLY OPERATION INTERFACE

SOLAR & LITHIUM IRON PHOSPHATE BATTERY

PORTABLE & EASY TO TRANSPORT

AUSTRALIAN DESIGNED & ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

Model	GP56k-H Eco Hybrid
Mast Height	25 feet
Mast Type	Hydraulic/Cable
Generator	2kW Hatz 28v DC

OPERATIONAL DATA

Wind Rating	62mph
Working Temperature	32 to 122°F
Stabiliser Supports	4 x Manual
Battery	24v 5.9kWh Lithium LiFePO4
Solar	1.32kWp
Solar Tilt	30° to 45°
Fuel Consumption	6.7 fl . oz/hr
Fuel Capacity	13.3 gallons

UNIT INFORMATION

Dimensions (Towing)	124" x 60" x 123" (LxWxH)
Dimensions (Deployed)	87" x 140" x 294" (LxWxH)
Dimensions (Stowed)	87" x 60" x 123" (LxWxH)
Weight (WET)	3,197lbs
Trailer Type	Single Axle
Tyre & Rim Size	215/70R15
Security	Hitch lock, security wheel nuts

© 2025 All information and imagery contained in this brochure is the property of Globe Power. This document is for informational purposes only. Globe Power reserves the right to make changes without further notice to any information herein. The content is provided as is and without express or implied warranties of any kind.